



**WEVER & DUCRÉ**  
LIGHTING

# DEEP 1.0 PAR16

112120B0

Project
Type
Notes
Quantity
Date

## GENERAL

Ceiling , Recessed  
 Black Matt  
 RAL 9005 <sup>a</sup>  
 IP20  
 Interior  
 Output: 445<sup>b</sup>, 465<sup>c</sup> lm  
 CIE flux code: 94 98 100 100 96

## LED

Lamp PAR16  
 Socket GU10  
 max. per socket 12.0 W  
 CRI ≥ 90

## ELECTRICAL

100 - 240 V  
 LED Inset 6.5 W  
 Class 2

## PHYSICAL

Diameter 84 mm  
 Height 108 mm  
 0.12 kg  
 wire springs


## CUTOUT

Diameter 76-79 mm  
 Min. ceiling thickness 4 mm  
 Max. ceiling thickness 27 mm  
 Recessed depth 115 mm


<sup>a</sup> Color may deviate slightly due to production conditions.  
<sup>b</sup> PAR16 LAMP 2700K CRI90  
<sup>c</sup> PAR16 LAMP 3000K CRI90



Round ceiling recessed downlight made from die-cast aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; installation without tools using wire springs; suitable for ceiling thickness of 4-27 mm; recessed depth 115 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 2; lamp not included;



## LIGHT DISTRIBUTION





WEVER & DUCRÉ  
LIGHTING

# DEEP 1.0 PAR16

112120B0

## LAMPS

### PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	ø50·60	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	ø50·60	9 0 1 2 2 8 B 5
2700K   >90 CRI   GU10	White	ø50·60	9 0 1 2 2 8 W 3
3000K   >90 CRI   GU10	White	ø50·60	9 0 1 2 2 8 W 5
2700K   >80 CRI   GU10	Silver	ø50·60	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	ø50·60	9 0 5 2 2 7 S 4