



**WEVER & DUCRÉ**  
LIGHTING

# DEEP

## IP44 1.0 PAR16

112620B0

Project

Type

Notes

Quantity

Date

### GENERAL

Ceiling, Recessed

Black Matt

RAL 9005<sup>a</sup>

Front IP44

Back IP20

IC rated

Interior

Output: 390<sup>b</sup>, 405<sup>c</sup> lm

CIE flux code: 94 98 100 100 85

### LED

Lamp PAR16

Socket GU10

max. per socket 12.0 W

CRI ≥ 90

### ELECTRICAL

100 - 240 V

LED Inset 6.5 W

Class 2

### PHYSICAL

Diameter 95 mm

Height 117 mm

0.16 kg

wire springs

### CUTOUT

Diameter 86-89 mm

Min. ceiling thickness 4 mm


Max. ceiling thickness 25 mm

Recessed depth 125 mm


<sup>a</sup> Color may deviate slightly due to production conditions.

<sup>b</sup> PAR16 LAMP 2700K CRI90


<sup>c</sup> PAR16 LAMP 3000K CRI90



Round ceiling recessed downlight made from die-cast aluminium; surface Black Matt; powder coated; matt texture; RAL 9005; installation without tools using wire springs; suitable for ceiling thickness of 4-25 mm; recessed depth 125 mm; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP44; Class 2; IC rated; UGR ≤ 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m<sup>2</sup>; lamp not included;



### LIGHT DISTRIBUTION



[112620B0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré apply.  
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ  
LIGHTING

# DEEP IP44 1.0 PAR16

112620B0

## LAMPS

### PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	ø50·60	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	ø50·60	9 0 1 2 2 8 B 5
2700K   >90 CRI   GU10	White	ø50·60	9 0 1 2 2 8 W 3
3000K   >90 CRI   GU10	White	ø50·60	9 0 1 2 2 8 W 5
2700K   >80 CRI   GU10	Silver	ø50·60	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	ø50·60	9 0 5 2 2 7 S 4