



WEVER & DUCRÉ
LIGHTING

RAY SUSPENDED 2.0 PAR16

227720L0

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling , Suspended
incl. 4.0 m suspension
Aluminium Brushed
IP20
Interior
Output: 375 lm
CIE flux code: 94 98 100 100 97

LED

Lamp PAR16
Socket GU10
max. per socket 12.0 W
CRI ≥ 80

ELECTRICAL


100 - 240 V
LED Inset 4.4 W
Class 1

PHYSICAL


Diameter 67 mm
Height 200 mm
0.54 kg



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Aluminium Brushed; inclusive adjustable cable suspension max. 4000mm in Signal Black; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; Class 1; lamp not included; ceiling base not included;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

RAY SUSPENDED 2.0 PAR16

227720L0

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø-H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50-60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50-60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50-60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50-60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50-60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50-60	9 0 5 2 2 7 S 4

SINGLE SUSPENSION

Invisible ceiling base

COLOUR	L-W (MM)	ORDERCODE
Black	140-66	9 0 0 1 5 1 9 5
White	140-66	9 0 0 1 5 1 9 6



Single base

TYPE	COLOUR	Ø-H (MM)	ORDERCODE
ceiling base round	Black	ø84-29	9 0 0 5 2 0 2 1
ceiling base round	White	ø84-29	9 0 0 5 2 0 2 2

Semi recessed base

TYPE	COLOUR	Ø-H (MM)	ORDERCODE
for shades without steel wire only	White	ø84-72	9 0 0 5 2 0 2 6
for shades without steel wire only	Black	ø84-72	9 0 0 5 2 0 2 7

WALL BASE

Wall Base

TYPE	COLOUR	Ø-H (MM)	ORDERCODE
for 1 luminaire	White	ø82-32	9 0 0 1 9 1 9 5
for 1 luminaire	Black	ø82-32	9 0 0 1 9 1 9 6

Cable Wall-Ceiling Bracket

COLOUR	Ø-H (MM)	ORDERCODE
White	ø16-30	9 0 0 1 9 1 9 7
Black	ø16-30	9 0 0 1 9 1 9 8



WEVER & DUCRÉ
LIGHTING

RAY SUSPENDED 2.0 PAR16

227720L0

MULTI SUSPENSION

Multiple base round

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
up to max. 4 luminaires	White	Ø123·44	9 0 0 5 2 0 0 5
up to max. 4 luminaires	Black	Ø123·44	9 0 0 5 2 0 0 6
up to max. 8 luminaires	White	Ø123·44	9 0 0 5 2 0 3 1
up to max. 8 luminaires	Black	Ø123·44	9 0 0 5 2 0 3 2

Multiple base linear

TYPE	COLOUR	L·W·H (MM)	ORDERCODE
up to max. 2 luminaires	White	600·30·45	9 0 0 5 2 0 0 7
up to max. 2 luminaires	Black	600·30·45	9 0 0 5 2 0 0 8
up to max. 3 luminaires	White	900·30·45	9 0 0 5 2 0 0 9
up to max. 3 luminaires	Black	900·30·45	9 0 0 5 2 0 1 0
up to max. 4 luminaires	White	1200·30·45	9 0 0 5 2 0 1 1
up to max. 4 luminaires	Black	1200·30·45	9 0 0 5 2 0 1 2
up to max. 5 luminaires	White	1500·30·45	9 0 0 5 2 0 1 3
up to max. 5 luminaires	Black	1500·30·45	9 0 0 5 2 0 1 4

OPTIONAL

Hook

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
standard multi suspension hook	Black	Ø3·83	9 0 0 5 2 0 2 4
standard multi suspension hook	White	Ø3·83	9 0 0 5 2 0 2 5
optional multi suspension hook	Black	Ø5·90	9 0 0 5 2 0 6 5
optional multi suspension hook	White	Ø5·90	9 0 0 5 2 0 6 6
for cable 4.25-5.5mm diameter	White	Ø15·35	9 0 0 5 2 0 7 9
for cable 4.25-5.5mm diameter	Black	Ø15·35	9 0 0 5 2 0 8 0