



WEVER & DUCRÉ
LIGHTING

STRANGE

trimless 2.0 PAR16

131220B0

Project	
Type	
Notes	
Quantity	
Date	

GENERAL

Ceiling , Recessed
Tilt max 35°
Rotation 355°
Black Matt
RAL 9005^a
IP20
Interior
Output: 845^b, 880° lm
CIE flux code: 94 98 100 100 92

LED

Lamp 2 x PAR16
Socket GU10
max. per socket 12.0 W
CRI ≥ 90

ELECTRICAL

100 - 240 V
LED Inset 6.5 W
Total insets 13.0 W
Class 2

PHYSICAL

Length 140 mm
Width 70 mm
Height 120 mm
0.7 kg
alu plasterkit

CUTOUT

Length 156 mm
Width 86 mm
Min. ceiling thickness 7 mm
Max. ceiling thickness 32 mm
Recessed depth 125 mm


^a Color may deviate slightly due to production conditions.

^b PAR16 LAMP 2700K CRI90


^c PAR16 LAMP 3000K CRI90



Rectangular ceiling recessed luminaire made from aluminium; surface Black Matt; powder coated, matt texture; RAL 9005; recessed depth 125 mm; lamp socket GU10; lamp type PAR16; 2x max. 12W; 100 - 240 V; 355° rotatable and 35° tiltable; degree of protection IP20; Class 2; lamp not included;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

STRANGE

trimless 2.0 PAR16

131220B0

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50·60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50·60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50·60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50·60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50·60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50·60	9 0 5 2 2 7 S 4

MOUNTING

Plasterkit

TYPE	L·W·H (MM)	ORDERCODE
STRANGE 2.0 SNEAK TRIMLESS 2.0	151·81·42	9 0 0 1 7 1 2 1

OTHER

Metal spring clip

TYPE	Ø (MM)	ORDERCODE
MR16 LED PAR16 max. 12W	59	9 0 0 1 9 7 0 0



Spring clip

TYPE	COLOUR	Ø (MM)	ORDERCODE
MR16 LED PAR16 max. 12W	Black	59	9 0 0 1 9 8 B 0
MR16 LED PAR16 max. 12W	Champagne	59	9 0 0 1 9 8 M 0
MR16 LED PAR16 max. 12W	White	59	9 0 0 1 9 8 W 0